

Technical parameters

Item	Specifications							
Model	ITL150							
Display size	15" 4:3							
Active area	304.128 (W) x 228.096 (H) mm							
Pixel pitch	0.297(mm) x 0.297 (mm)							
Native resolution	1024x768@60Hz							
Colors	16.7M							
Brightness(typical)	LED panel: 300 (cd/m ²)							
	Display: 258 (cd/m ²)(With PCAP Touchscreen)							
Contrast ratio(typical)	700:1							
Response time(typical)	8 ms							
Viewing angle(typical)	R/L:80/80° U/D:70/60°							
Input interface	VGA, DVI							
Resolution supported	No	Format	(KHz)	Polarity	(Hz)	Polarity	(MHz)	Remark
	1	640 x 480	31.47	-	59.94	-	25.175	VGA
	2	800 x 600	37.88	+	60.32	+	40.000	VESA
	3	1024 x 768	48.36	-	60.00	-	65.000	VESA
OSD	Contrast, Brightness, Horizontal vertical image size and position, Color temperature, The language selection, RESET, Exit OSD.							
Privacy filter (optional)	30°(L/R)							
Item	Touch Specifications							
Touch screen	15 " PCAP							
Touch point	10 points							
Touch accuracy	2mm							
Minimum touch body	Ø7mm							
Touch activation force	10g							
Touch response time	10ms (typ)							
IC	ILITeK							
Material	2mm strengthen glass							
Surface durability	Mohs' 7H							
Light transmission	86%							
Touch resolution	4096*4096							
Input method	Finger, Touch pen							
Expected life performance	35,000,000 times							

Technical parameters

Item	Other Specifications			
Power supply	DC: +12V ±5% (Adapter input:AC 100V-240V)			
Power consumption	Max: 12W			
	Standby: < 0.5 W			
IP(touch screen with frame)	IP 65			
MTBF	50,000h			
Dimensions	Product: 348.4mm*272.4mm*42.0mm			
	Package: 430.0mm*380.0mm*154.0mm			
Weight	Product: 4. 0kg			
	Package:5.0kg			
Temperature	Operating: 0° C ~ 40°C			
	Storage: -20° C ~ 60°C			
Humidity	Operationg: 20%~80%			
	Storage: 10%~90%			
Accessories	Signal Cables	Connector	D-SUB 15Pin	
		Length	1.8 m ± 30mm	
		Color	Blue	
	Power Cord	Type	Comply with local safety regulations	
		Length	1.8 m ± 30mm	
		Color	Black	
	Adapter	Type	M120300P911(12V 3A)	
		Color	Black	

Record Of Revisions

Model:ITL150

Version and Date	Page	Old Description	New Description	Remark
A0 2016/01/21	ALL	First Edition For Customer		