

## Display - Monitor



### 21.5" Medical Display

- ✦ IP65 in front & IPx1 whole unit
- ✦ ALS (optional)
- ✦ Calibration mode(optional)
- ✦ 20 meter DVVHDMI long cable solution

### + Spec

I/O	
RS232	Optional
Input Interface	1 x VGA 1 x DVI 1 x HDMI 1 x Display Port
Mechanical & Environmental	
Power Type	AC In
Operating Temp	0°C ~ 40°C (32°F ~ 104°F)
Storage Temp	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	10%~90% Relative Humidity, Non-condensing
Weight	5.5 Kgs
Construction	Plastic
Mounting Kit	Stand (Optional) VESA Mount kit (Optional) Wall Mount kit (Optional)
Vibration Test	With SSD/mSATA: 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Test	With SSD/mSATA: 10Grms, IEC 60068-2-27, Half Sine, 11ms
System Fan	Fanless
Dimension	521.07 x 326.07 x 56.5 mm
Certifications	
Certification Information	CE(EN60601-1,EN60601-1-11) FCC certified cTUVus certified

### + Ordering

MSBP2111AMC01  
MSBP2111AMC with AG Glass

MSBP2111AMC02  
MSBP2111AMC with PCAP