

MSBP2111LMC

Industrial Computer Source
(Deutschland) GmbH

Medical Display



- ✕ IP65 in front & IPx1 whole unit
- ✕ ALS (optional)
- ✕ Calibration mode(optional)
- ✕ 20 meter DV/HDMI long cable solution

+ Spec

I/O	
RS232	Optional
Input Interface	1 x VGA 1 x DVI 1 x HDMI 1 x Display Port
Mechanical & Environmental	
Power Type	24V DC In
Operating Temp	0°C ~ 40°C (32°F ~ 104°F)
Storage Temp	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	10%~90% Relative Humidity, Non-condensing
Weight	5.5 Kgs
Construction	Plastic
Mounting Kit	Stand (Optional) VESA Mount kit (Optional) Wall Mount kit (Optional)
Vibration Test	With SSD/mSATA: 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Test	With SSD/mSATA: 10Grms, IEC 60068-2-27, Half Sine, 11ms
System Fan	Fanless
Dimension	521.07 x 326.07 x 56.5 mm
Certifications	
Certification Information	CE(EN60601-1,EN60601-1-11) FCC certified cTUVus certified
Panel	
LCD Size	21.5"
Display Type	Full HD
Resolution	1920 x 1080
Luminance	210 Cd/m2
Contrast ratio	1000:1
Viewing angle	89/89 Deg. Horizontal & Vertical
Backlight	LED
Touch Type	Projective Capacitive
AG Protection Glass	Yes
DICOM compliant	Yes

+ Ordering

MSBP2111LMC01
MSBP2111LMC with AG Glass

MSBP2111LMC02
MSBP2111LMC with AG PCAP