

AI Box PC



Features

- Fully support NVIDIA® Jetson Xavier™ NX
- 8x 10/100 MbE with PoE
- 1x GbE, 2x USB 3.0, 1x 4Kp60 HDMI output
- 20 pins with 1x UART, 2x I2C
- 1x RS-485 (3 pins), 1x Micro-B USB 2.0 for recovery
- 1x mPCIe (Host Interface: USB 2.0)
- Operating temperature: 0°C ~ 65°C (without HDD, with No-Air-Flow)
- Compact fanless chassis with AVerCooler technology

AVerMedia's AVerAI NX213B Box PC of NVIDIA® Jetson Xavier™ NX is designed as an A.I. NVR (Network Video Recorder) for intelligent surveillance system.

This product provides 8-channel PoE (PSE) ports for IP cameras, a SATA port for storage, 1x mPCIe, 2x USB 3.0, 1x microphone input, 1x speaker output, 1x RS-485 and 20-pin expansion header (I2C, SPI, UART, I2S), 1x HDMI 2.0 out.

Benefiting from the Jetson Xavier™ NX and DeepStream SDK, it can simultaneously decode and analyze 8-channel 1080p60 IP camera videos.

By using AVerCooler WaveFin technology, the latest edge computing module, NVIDIA® Jetson Xavier™ NX, NX213B can operate in the environment up to 65°C without airflow.

AVerAI NX213B Box PC is designed as an application ready platform for multiple applications to improve the performance, flexibility and time to market. With NX213B, software developers not only can deploy their deep learning software on this system but also can market their software in a Box PC as a complete solution. This can greatly help simplify the efforts and processes of the system integration in launching their A.I. solution into the market faster.

Embedded Vision Solutions for NVIDIA Jetson

AVerMedia offers 3 categories of Embedded Vision Solutions for deep learning application on the edge devices, with the support of NVIDIA Jetson family, battery power, HDMI/VGA/3G-SDI/Composite video sources, and the direct technical support for developers.

- Standard and customized of Nano/Tegra/Xavier NX/AGX Xavier carrier boards
- Standard and customized Nano/Tegra/Xavier NX/AGX Xavier application-ready systems
- Software design service of Linux BSP, driver, OpenCV, VisionWorks, and cuDNN.

Why AVerMedia

- As NVIDIA® PREFERRED solution provider, AVerMedia gets the direct support from NVIDIA. We are able to offer technical support in 24 hours to help your project success.
- Support full range of NVIDIA Jetson modules, including Nano, Tegra, Xavier NX, and AGX Xavier.
- Support various video input sources from IP camera, USB camera, MIPI camera, and capture cards supporting HDMI/VGA/3G-SDI/Composite video sources.
- Provide customization services of HW, PCB, chassis, BSP, driver, and UX/UI/ID/ME design.
- Supports 65°C/149°F operating temperature in the No-Air-Flow environment for fanless system designed by using AVerCooler technologies.
- Provide flexible user-configured security to protect the SW.

Specifications

Type	Box PC with AVerCooler WavieFin passive cooling system
NVIDIA GPU SoC Module Compatibility	NVIDIA® Jetson Xavier™ NX module
Networking	1x GbE RJ-45 8x 10/100 MbE RJ-45 with PoE (Max for the first 4 ports is 15.4W and total power budget is 90W)
Display Output	1x HDMI 2.0a/b Type-A supports maximum resolution 3840x2160 at 60Hz
Temperature	Operating Temperature 0°C ~ 65°C Storage Temperature -40°C ~ 85°C Relative Humidity 40 °C @ 95%, Non-Condensing
USB	1x USB 2.0 Micro-B for recovery 2x USB 3.0 Type-A (USB 3.2 Gen1 x 1)
Storage	16GB e.MMC v5.1
GPIO Expansion	1x 3.3V UART, 2x I2C, 5x GPIOs
Input Power	54V/2.78A
Buttons	Power and Recovery Button (each with a RGB tri-color LED)
RTC Battery	Support RTC battery and Battery Life Monitoring by MCU
Chassis Dimension/ Weight	W:190mm x L:175mm x H:80mm (W:220 mm with mounting ears) Weight: 2.75 Kg
Certifications	CE, FCC

*All specifications are subject to change without prior notice.